

# B&B Machines

8, Sidhdhapura Estate, Nr. Hanuman Temple, Opp. DGP Windsor, G. I. D. C. Vatva, Ahmedabad - 382 445. Gujarat. INDIA  
 Phone : 91-79-64507809 Email : info@bakaraniabrothers.com URL : www.bakaraniabrothers.com

## Technical features

- Vertical Axis, vertical carriers
- Heat treated braided plate and track
- Heat treated horn gears and horn plate
- Overload motor protection
- Line forward/ reverse jog
- Automatic machine shut off for broken end, empty bobbin

## Optional attachment

- Aluminum enclosure
- Meter Counter

## Application

- Rope for bigger size
- Climbing Rope
- Sleaving

## Solid Cord Braiding Machine



## Technical Specification

Description	BMSC-1/09-100	BMSC-1/12-100	BMSC-1/18-100	BMSC-2/09-100	BMSC-2/12-100	BMSC-2/18-100
Length (L)	1450	1290	1530	1310	1500	1150
Depth (D)	450	400	410	380	430	490
Height (H)	1350	1350	1350	1350	1400	1400
No of Heads	12	06	04	03	03	02
Carriers per Head	03	09	13	17	21	25
Horn Gear Speed	300	300	300	300	300	300
Bobbin Size	42x120	42x120	42x120	42x120	42x120	42x120
Control Volume	135	135	135	135	135	135
Carrier Tension	1 N ~ 10 N	1 N ~ 10 N	1 N ~ 10 N	1 N ~ 10 N	1 N ~ 10 N	1 N ~ 10 N
Motor (Ph/ Kw/ V)	3/ 1.10/ 415	3/ 1.50/ 415	3/ 1.50/ 415	3/ 2.9/ 415	3/ 2.1/ 415	3/ 2.9/ 415
<b>Option</b>						
Take off on Drum	●	●	●	●	●	●
Empty Bobbin Control	●	●	●	●	●	●
Meter Counter	○	○	○	○	○	○
Housing with Safety Doors	○	○	○	○	○	○
Infinitely Variable Speed Control	○	○	○	○	○	○
● Standard ○ Option						
Material	Asbestos/ non-asbestos					

Standard Supply Voltage: - AC 3-Phase & Neutral, 415 Volt, 50 Hz

The manufacturer reserves right to change design/specifications because of continuous development.  
 Accessories/attachement shown on the photograph may not be the part of standard machine.  
 Maximum speed shown above is indicative only and actual output will depend on the type of fiber.