

B&B Machines

8, Sidhdhapura Estate, Nr. Hanuman Temple, Opp. DGP Windsor, G. I. D. C. Vatva, Ahmedabad - 382 445. Gujarat. INDIA
 Phone : 91-79-64507809 Email : info@bakaraniabrothers.com URL : www.bakaraniabrothers.com

Technical features

- Fluent start
- Settable winding speed
- Regulation of winding lead
- Requested diameter of winding is settable by end switch
- Tension regulator

Optional attachment

- Length counter with length pre-selection
- Automatic machine shut off for broken end or empty spool

Application

- Cross Winding of Bobbin



Spool Winding Machine



Technical Specification

Description	WM-02	WM-04	WM-06
Length (L)	1220	2440	3660
Depth (D)	715	715	715
Height (H)	1200	1200	1200
No. of Winding Position	02	04	06
Traverse (mm)	192	192	192
Speed Control (rpm)	540	540	540
Max. Bobbin Diameter (mm)	100	100	100
Motor (Ph/ Kw/ V)	3/ 0.75/ 415	3/ 1.5/ 415	3/ 2.2/ 415
Option			
Yarn Break Control	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Length Counter	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Infinitely Variable Speed Control	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
● Standard ○ Option			
Material	Asbestos		

Standard Supply Voltage: - AC 3-Phase & Neutral, 415 Volt, 50 Hz

The manufacturer reserves right to change design/specifications because of continuous development. Accessories/attachment shown on the photograph may not be the part of standard machine. Maximum speed shown above is indicative only and actual output will depend on the type of fiber.